



Tipton Road Dudley West Midlands DY1 4SQ United Kingdom

Tel. +44 (0)121 557 1188 Email: stainlessfittings@sfluk.co.uk

Customer Name & Example Material Certificate

Code ****

Customer Order No ****

Our Order No ****

Despatch Date ****

Internal Ref No **** Certificate To: EN10204:2004 3.1

Material Grade 316L

Surface Finish SAT POL OD, 0.38um MAX ID AFTER ELECTROPOLISH, SF4

Qty Description Product Code

2 1.5" EQ SHT OUT TEE DT-4.1.2-5

Spec. ASTM A240											
Heat No	С	Si	S	P	Mn	Cr	Ni	Mo	Ti	Со	
36904	0.024	0.560	0.006	0.032	1.470	17.000	10.100	2.030	0.000	0.000	
	Yield	Yield		Ultimate		Elongation		Reduction		Hardness	
Notes	Tensile N/mm		Tensile N/mm		A%		Of Area %				
316L			594						86 HRB		
Spec. ASTM A479											
Heat No	С	Si	S	P	Mn	Cr	Ni	Mo	Ti	Со	
6J066501A	0.022	0.390	0.008	0.027	1.800	16.870	10.020	2.020	0.000	0.000	
	Yield	Yield		Ultimate		Elongation		Reduction		Hardness	
Notes	Tensile	Tensile N/mm		Tensile N/mm		A%		Of Area %			
316L			600		57		68		78 HRB		
Spec. ASTM A269/A	270										
Heat No	С	Si	S	P	Mn	Cr	Ni	Mo	Ti	Со	
889582	0.013	0.410	0.012	0.029	1.520	16.640	10.080	2.180	0.000	0.000	
	Yield	Yield		Ultimate		Elongation		Reduction		Hardness	
Notes		Tensile N/mm		Tensile N/mm		A%					
316L	0.6	267 573		55.8				81.4 HRB			

Stainless Fittings certify that the items above have been manufactured, procured, inspected and tested in accordance with our ISO 9001 registered Quality System and conform to the stated specification. The items comply with the customer order requirement as acknowledged by Stainless Fittings Limited.

To guard against the remote possibility that Transmissible Spongiform Encephalopathy (TSE) may be passed into the supply chains of products for human consumption, Stainless Fittings has undertaken an audit of materials, manufacturing processes and process consumables. Stainless Fittings declare that the materials used in process contact products supplied do not contain animal derivatives in any part of their design.

Release Authority Signed:

